

KAT-A 5454

Product characteristics and benefits

- Position indicator (without limit switch)
- Suitable for mechanical and inductive limit switches
- Retrofittable to protect the position indicator against damage during the construction stage
- Suitable for VAG BETA[®] 200 and EKO[®]plus Gate Valves (Note: also order handwheel for gate valve)
- Suitable for VAG IKO[®]plus Gate Valves (handwheel included in the scope of supply)
- Suitable for low-corrosion environments, e.g. in sprinkler systems
- For indoor installation in rooms with normal atmospheric humidity and no dirt

Materials

- Adapter ring: Ductile iron EN-GJS-400-15 (GGG-40)
- Standard parts: Stainless steel
- Indicator display: Plastic (POM)
- Stem cover: Stainless steel

Corrosion protection

- Adapter ring: Epoxy coating

Versions

- Standard version as described
- With pin indicator and electrical position indicator with one mechanical limit switch for OPEN and CLOSED position (please specify in order) to EN 50049
- With pin indicator and electrical position indicator with two mechanical limit switches for OPEN and CLOSED position to EN 50049
- With pin indicator and inductive position indicator with one limit switch for OPEN and CLOSED position (please specify in order) to EN 50049
- With pin indicator and inductive position indicator with two limit switches for OPEN and CLOSED position to EN 50049



Note

For proper installation and safe operation please follow the installation and operation instructions:

“Installation and Operating Instructions for Valves”